

PTO Murat Makina San ve Tic. Ltd. Şti.





PTO

CATALOG (PTO Murat Makina Sorted By Product Code)





PTO Code 005AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 80.101.0 E 90	Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,32 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 006AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 60-6 MERCEDES G 71-6 MERCEDES G 85-6 MERCEDES G 90-6	Gear Type : Flat PTO Type : Single Thread Torque Nm : 600 Power Kw : 62 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 5,70	
PTO Code 007AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MAN 9.136 WOLKSWAGEN 9.136	Gear Type : Helix PTO Type : Double Thread - Pump Side Sealing Seal Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 008AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model FOTON BJ 1061 OTOKAR ATLAS WANIER 6 S 51 B WLY 6 S 51 B - 40 B WLY6S51 B	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,13 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,60	
PTO Code 011AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HINO LX 06 S ISUZU LX 06 S	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	



PTO Code 012AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 44 ZF 6 AS 700 ZF 6 S 36 ZF 6 S 700 ZF 6 S 850	Gear Type : Flat PTO Type : Single Thread Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 014AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 3/50 MERCEDES G 5/75 MERCEDES G 51302 MERCEDES G 52302	Gear Type : Flat PTO Type : Single Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 5,80	
PTO Code 014BL	Pump Side Connection Type of PTO Shaft Output Pin Hole	Main Transmission Model MERCEDES G 3/50 MERCEDES G 5/75 MERCEDES G 51302 MERCEDES G 52302	Gear Type : Flat PTO Type : Single Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	
PTO Code 016AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 4 110 MERCEDES G 4 65 MERCEDES G 4 90 MERCEDES G 4 95 MERCEDES G 6 90	Gear Type : Flat PTO Type : Single Thread Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	
PTO Code 017AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model BMC 415 JAC LC 6 T 540 B JAC 1008	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 21 Output Ratio 1000 Rpm : 1:1,04 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,50	



PTO Code 034AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON ESO 14409 EATON FS 6109 A EATON FS 6109 B EATON FS 6109 DT EATON FS 6209 EATON FS 6209 EATON FS 6309 A EATON FS 8209 A EATON FS 8209 B EATON FS 8209 EHD EATON FS 8309 A EATON FSO 6109 A EATON FSO 6109 A	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:0,83 Mounting Location : Left Front Cover Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 038AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model VOLVO R 70 VOLVO SR 70 VOLVO SR 71 VOLVO SR 72	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,00	
PTO Code 046AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MACK TRD 670	Gear Type : Flat PTO Type : Double Thread Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,25 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00	
PTO Code 048AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES 2067	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code 049AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 14613 A EATON 11609 A EATON 11613 A EATON 12513 A EATON 14609 B EATON FS 10209 A EATON RT 9509 A FULLER	Gear Type : Flat PTO Type : Double Thread Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,08 Mounting Location : Bottom Cover Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 15,00	




PTO Code 051BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI M 1 S 5 HYUNDAI M 2 S 5 HYUNDAI M 3 S 5 MITSUBISHI M 1 S 5 MITSUBISHI M 2 S 5 MITSUBISHI M 3 S 5	Gear Type : Flat PTO Type : Single Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	
PTO Code 054AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model VOLVO GR 51 VOLVO GR 52 VOLVO R 50 VOLVO R 51 VOLVO R 52 VOLVO SR 52	Gear Type : Flat PTO Type : Double Thread Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 9,00	
PTO Code 067BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 2-24 MERCEDES 309	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 068BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON T 5 V 2245 EATON T 5 V 2246 EATON T 5 V 2247 EATON T 5 V 2248 EATON T 5 V 2262 EATON T 5 X 2245 EATON T 5 X 2246 EATON T 5 X 2247 EATON T 5 X 2262 EATON T 5 X 2276 EATON T 5 X 2292	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,44 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 071BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model KIA 3500 KIA COBRA MAZDA	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 9,00	





PTO Code 072AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model TURNER T 5 C 4001 TURNER T 5 C 4084 TURNER T 5 C 4003 TURNER T 5 C 4161 TURNER T 5 C 4006 TURNER T 6 H 4085 TURNER T 5 C 4050 TURNER T 6 H 4086 TURNER T 5 C 4058 TURNER T 6 H 4087 TURNER T 5 C 4060 TURNER T 5 C 4062 TURNER T 5 C 4068		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,12 Mounting Location : Left and Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	
PTO Code 073AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 542 CMA EATON 542 CMD EATON 542 SMJ EATON 542 SMO EATON 570 SMS HEMA 542 SMJ HEMA 570 SMS		Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,36 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,70	
PTO Code 074AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMA EATON 475 SMO HEMA 475		Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left and Right Side Control System : Pneumatic PTO Shaft Rotation : Right and Left — (Pump Shaft Rotation : Left And Right) Weight Kg. : 10,70	
PTO Code 075AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SML EATON 475L		Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 077AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 1.120.060 IVECO 1.128.060 IVECO 1.128.025 IVECO 28.046 IVECO 1.128.030 IVECO 1.128.035 IVECO 1.128.042 IVECO 1.128.046 IVECO 1.128.050 IVECO 1.128.055		Gear Type : Flat PTO Type : Single Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	

PTO Code 079AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 3105 DT EATON 3106 DT EATON 4105 A EATON 4106 A EATON 5109 DT EATON 5206 A EATON 6406 EATON FS 5209 A EATON FSO 10209 EATON FSO 10309 EATON FSO 4106 B EATON FSO 5206 B EATON V 4106 IVECO FSO 5206 B	Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Left Rear Cover Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11	
PTO Code 081BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HINO 350 5 S HINO LH 05 S HINO MG 06 HINO MG 10 S HINO MH 06 S TOYOTA LH 05	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 082BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MRP 58 P ISUZU MRP 59 ISUZU MSA 5 G ISUZU MSA 5 P ISUZU MSA 5 R	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,32 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 083AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 542 CMA EATON 542 CMD EATON 542 SMJ EATON 542 SMO EATON 570 SMS HEMA 542 SMJ HEMA 570 SMS	Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,50 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 086AD	Pump Side Connection Type of PTO Flanged - Coupling	Main Transmission Model MAZ 236 MAZ 5334	Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	


<u>PTO Code</u> 087AE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> EATON 540 HEMA 540	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
<u>PTO Code</u> 088BE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> BEDFORD KBC 10	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 190 Power Kw : 19 Output Ratio 1000 Rpm : 1:1,47 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
<u>PTO Code</u> 092A	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> EATON 14613 A EATON 11609 A EATON 11613 A EATON 12513 A EATON 14609 B EATON FS 10209 A EATON RT 9509 A FULLER	Gear Type : Flat PTO Type : Single Thread Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : Mounting Location : PTO Control System : PTO Shaft Rotation : Weight Kg. : 12,00	
<u>PTO Code</u> 094AE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> IVECO 1.128.020 IVECO 1.128.028 IVECO 1.128.031 IVECO 1.128.128 IVECO 2828.5 IVECO 35.9 IVECO 65.9	Gear Type : Flat PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,30	
<u>PTO Code</u> 094BE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> IVECO 1.128.020 IVECO 1.128.028 IVECO 1.128.031 IVECO 1.128.128 IVECO 2828.5 IVECO 35.9 IVECO 65.9	Gear Type : Flat PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,30	


<u>PTO Code</u> 096AE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> ZF S 5- 42 7,552-1.00	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,12 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
<u>PTO Code</u> 097AE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> EATON FS 5005 A EATON FS 5205 A	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 230 Power Kw : 24 Output Ratio 1000 Rpm : 1:1,19 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,80	
<u>PTO Code</u> 098AE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> EATON FS 5005 A EATON FS 5205 A	Gear Type : Rigt Helix PTO Type : Double Thread Torque Nm : 230 Power Kw : 24 Output Ratio 1000 Rpm : 1:1,27 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,80	
<u>PTO Code</u> 099AE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> EATON FS 5005 A EATON FS 5205 A	Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,40 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,50	
<u>PTO Code</u> 100BE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> KIA 100 CERES	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,28 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,50	




PTO Code 101AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 16 S 109 - 12.92 ZF 16 S 109 - 13.30 ZF 16 S 109 - 13.42 ZF 9 S 109 - 12.92 ZF 9 S 109 - 13.42		Gear Type : Right Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,31 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 102BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	EATON T 5 V 2245 EATON T 5 V 2246 EATON T 5 V 2247 EATON T 5 V 2248 EATON T 5 V 2262 EATON T 5 X 2245 EATON T 5 X 2246 EATON T 5 X 2247	EATON T 5 X 2262 EATON T 5 X 2276 EATON T 5 X 2292	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 103BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MSB 5 M ISUZU MSB 5 P ISUZU MSB 5 S		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 10,60	
PTO Code 106BL	Pump Side Connection Type of PTO Shaft Output Pin Hole	EATON T 5 V 2245 EATON T 5 V 2246 EATON T 5 V 2247 EATON T 5 V 2248 EATON T 5 V 2262 EATON T 5 X 2245 EATON T 5 X 2246 EATON T 5 X 2247	EATON T 5 X 2262 EATON T 5 X 2276 EATON T 5 X 2292	Gear Type : Left Helix PTO Type : Single Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 7,00	
PTO Code 110AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMLX IVECO 475 SML X L		Gear Type : Right Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,25 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	


PTO Code 110BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMLX IVECO 475 SML X L	Gear Type : Right Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,25 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 111AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMLX IVECO 475 SML X L	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,25 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 111BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMLX IVECO 475 SML X L	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,25 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 113BL	Pump Side Connection Type of PTO Shaft Output Pin Hole	Main Transmission Model BEDFORD KBC 10	Gear Type : Left Helix PTO Type : Single Thread Torque Nm : 240 Power Kw : 25 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 7,00	
PTO Code 116BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 309 MERCEDES 309	Gear Type : Left Helix PTO Type : Single Thread Torque Nm : 240 Power Kw : 25 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 7,00	




PTO Code 125BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON T 5 V 2040 EATON T 5 V 2041 EATON T 5 X 2071 SPICER T 5 V 2040 SPICER T 5 V 2041 SPICER T 5 X 2071 TURNER T 5 V 2043 TURNER T 5 V 2052		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 130AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 S 109 - 12.92 ZF 16 S 109 - 13.30 ZF 16 S 109 - 13.42 ZF 9 S 109 - 12.92 ZF 9 S 109 - 13.42		Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,00	
PTO Code 131AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 S 109 - 12.92 ZF 16 S 109 - 13.30 ZF 16 S 109 - 13.42 ZF 9 S 109 - 12.92 ZF 9 S 109 - 13.42		Gear Type : Helis PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,70	
PTO Code 134AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMA EATON 475 SMLX EATON 475 SMO HEMA 475 IVECO 475 SML X L		Gear Type : Flat PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 9,00	
PTO Code 136AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36	ZF 16 S 130	Gear Type : Flat PTO Type : Single Gear Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 3,70	
		MERCEDES G 3 45	ZF 16 S 160		
		MERCEDES G 3 55	ZF 16 S 190		
		MERCEDES G 3 60	ZF 16 S 220		
		MERCEDES S 6-36	ZF 6 AS 1000 TO ZF 6 S 800		



PTO Code 139AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 3 36 ZF 16 S 130 MERCEDES G 3 45 ZF 16 S 160 MERCEDES G 3 55 ZF 16 S 190 MERCEDES G 3 60 ZF 16 S 220 MERCEDES S 6-36 ZF 6 AS 1000 TO ZF 6 S 800		Gear Type : Flat PTO Type : Double Gear Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,24 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 141BL	Pump Side Connection Type of PTO Shaft Output Pin Hole	Main Transmission Model EATON 3105 DT EATON FSO 10209 EATON 3106 DT EATON FSO 10309 EATON 4105 A EATON FSO 4106 B EATON 4106 A EATON FSO 5206 B EATON 5109 DT EATON V 4106 EATON 5206 A IVECO FSO 5206 B EATON 6406 EATON FS 5209 A		Gear Type : Flat PTO Type : Single Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	
PTO Code 142ADF	Pump Side Connection Type of PTO Flanged - Coupling	Main Transmission Model MERCEDES G 3-65 MERCEDES G 3-90		Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 280 Power Kw : 29 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 143AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON ESO 14409 EATON FS 8209 B EATON FS 6109 A EATON FS 8209 EHD EATON FS 6109 B EATON FS 8309 A EATON FS 6109 DT EATON FSO 6109 A EATON FS 6209 EATON FSO 6109 A EATON FS 6209 EATON FS 6109 AV EATON FS 6309 A EATON FS 8209 A		Gear Type : Flat PTO Type : Double Gear Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Left Rear Cover Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 147AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 9 S 75		Gear Type : Right Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	


PTO Code 153AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model TURNER T 5 A 3016 TURNER T 5 A 3017	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,12 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	
PTO Code 154AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 44 ZF 6 AS 700 ZF 6 S 36 ZF 6 S 700 ZF 6 S 850	Gear Type : Flat PTO Type : Doble Gear Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,24 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 155AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 16 K 109 - 11.86 ZF 16 S 109 - 11.86 ZF 16 S 109 - 13,53 ZF 9 S 109 - 10.24	Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,40	
PTO Code 156AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model FORD 1010	Gear Type : Helix PTO Type : Double Gear Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,20	
PTO Code 158BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES MB 700 MERCEDES MB 800 ZF S 5- 42	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	




PTO Code 159AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 9 S 75	Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,00	
PTO Code 160BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	ISUZU 5 R W 530 ISUZU MXA 5 R ISUZU NXA 5 R	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,32 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,60	
PTO Code 161AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	IVECO 2845.5 IVECO 2845.6 IVECO 2855.6	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,60	
PTO Code 161BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	IVECO 2845.5 IVECO 2845.6 IVECO 2855.6	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,60	
PTO Code 165AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	MACK 700 ST MACK DM 600 SX MACK DM 609 S MACK F 700 ST MACK F 700 T MACK R 607 S MACK TRD 722 MACK TRQ 7220	Gear Type : Flat PTO Type : Three Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,57 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 17,30	

PTO Code 166AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model EATON TS 11612 EATON TS 15612 EATON TS 43612 IVECO TS 11612 IVECO TS 13612 IVECO TS 16612		Gear Type : Düz PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,10	
PTO Code 167BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI MO 35 S 5 MITSUBISHI MO 35 S 5 MITSUBISHI MO 35 T 6		Gear Type : Right Helix PTO Type : Single Gear Torque Nm : 150 Power Kw : 15 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,50	
PTO Code 169AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 155-16 MERCEDES G 155-9 MERCEDES G 180-16 MERCEDES G 210-16		Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,00	
PTO Code 170AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	TURNER T 5 C 4001 TURNER T 5 C 4003 TURNER T 5 C 4006 TURNER T 5 C 4050 TURNER T 5 C 4058 TURNER T 5 C 4060 TURNER T 5 C 4062 TURNER T 5 C 4068	TURNER T 5 C 4084 TURNER T 5 C 4161 TURNER T 6 H 4085 TURNER T 6 H 4086 TURNER T 6 H 4087	Gear Type : Flat PTO Type : Double Gear Torque Nm : 470 Power Kw : 49 Output Ratio 1000 Rpm : 1:0,95 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 172BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2826.5		Gear Type : Right Helix PTO Type : Double Gear Torque Nm : 165 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,10 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	



PTO Code 173AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model KAMAZ	Gear Type : Flat PTO Type : Double Gear Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left and Right Side Control System : Pneumatic PTO Shaft Rotation : Right and Left — (Pump Shaft Rotation : Left And Right) Weight Kg. : 12,00	
PTO Code 174AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model SAMSUNG SM 510 TONGIL	Gear Type : Flat PTO Type : Single Gear Torque Nm : 170 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 9,00	
PTO Code 176BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MITSUBISHI MO 25 S5	Gear Type : Right Helix PTO Type : Single Gear Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,20	
PTO Code 186AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model RENAULT B 18200 L	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,72 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 21,00	
PTO Code 188AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MBJ 5 J ISUZU MBJ 6 U ISUZU MBP 6 P	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 290 Power Kw : 30 Output Ratio 1000 Rpm : 1:1,30 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00	


PTO Code 188BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MBJ 5 J ISUZU MBJ 6 U ISUZU MBP 6 P		Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 290 Power Kw : 30 Output Ratio 1000 Rpm : 1:1,30 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00	
PTO Code 189BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON FS 2305 A		Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:0,96 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 190AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	EATON 3105 DT EATON 3106 DT EATON 4105 A EATON 4106 A EATON 5109 DT EATON 5206 A EATON 6406 EATON FS 5209 A	EATON FSO 10209 EATON FSO 10309 EATON FSO 4106 B EATON FSO 5206 B EATON V 4106 IVECO FSO 5206 B	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,07 Mounting Location : Left Front Cover Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	
PTO Code 192AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model EATON RTS 12316 A EATON 20672		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,60	
PTO Code 194AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	ZF 16 S 109 - 12.91 ZF 16 S 109 - 13.31 ZF 16 S 109 - 13.41 ZF 9 S 109 - 12.91 ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41	ZF 9 S 1110 - 12.73 ZF 9 S 1110 TD ZF 9 S 1115 / 12.73 ZF 9 S 1310 TO	Gear Type : Right Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,50 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,60	

PTO Code 195BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MITSUBISHI MO 60 S 6	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 280 Power Kw : 29 Output Ratio 1000 Rpm : 1:1,10 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 202AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 3/50 MERCEDES G 5/75 MERCEDES G 51302 MERCEDES G 52302	Gear Type : Helix PTO Type : Double Gear Torque Nm : 220 Power Kw : 23 Output Ratio 1000 Rpm : 1:1,31 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,00	
PTO Code 207AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2870.9	Gear Type : Helix PTO Type : Double Gear Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 212AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 S 109 - 12.91 ZF 9 S 1110 - 12.73 ZF 16 S 109 - 13.31 ZF 9 S 1110 TD ZF 16 S 109 - 13.41 ZF 9 S 1115 / 12.73 ZF 9 S 109 - 12.91 ZF 9 S 1310 TO ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41	Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 280 Power Kw : 29 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,80	
PTO Code 213BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2830.5 IVECO 5 S 200 IVECO 5 S 300 ZF 5 S 200 ZF 5 S 270 VO ZF 6 S 350	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,50	

PTO Code 214AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2845.5 IVECO 2845.6 IVECO 2855.6		Gear Type : Right Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,22 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,20	
PTO Code 215AC2 215AE	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 542 CMA EATON 542 CMD EATON 542 SMJ EATON 542 SMO EATON 570 SMS HEMA 542 SMJ HEMA 570 SMS		Gear Type : Right Helix PTO Type : Double Gear Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,31 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 9,40	
PTO Code 217AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 100-1 MERCEDES G 100-12 MERCEDES G 100-13 MERCEDES G 100-2 MERCEDES G 100-9 MERCEDES G 140-6 MERCEDES G 140-8		Gear Type : Flat PTO Type : Single Gear Torque Nm : 520 Power Kw : 54 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,00	
PTO Code 218AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 131-9 MERCEDES G 141-9 MERCEDES G 211-12 MERCEDES G 211-16 MERCEDES G 221-9 MERCEDES G 230-12 MERCEDES G 230-16 MERCEDES G 240-16	MERCEDES G 260-16 MERCEDES G 280-16 MERCEDES G 281-12 MERCEDES G 330-12	Gear Type : Düz PTO Type : Single Gear - Cardan Shaft Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,40	
PTO Code 220AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,10	

PTO Code 221AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model EATON ESO 14409 EATON FS 6109 A EATON FS 6109 B EATON FS 6109 DT EATON FS 6209 EATON FS 6209 EATON FS 6309 A EATON FS 8209 A		EATON FS 8209 B EATON FS 8209 EHD EATON FS 8309 A EATON FSO 6109 A EATON FSO 6109 A EATON FS 6109 AV	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,00	
PTO Code 222AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model EATON 3105 DT EATON 3106 DT EATON 4105 A EATON 4106 A EATON 5109 DT EATON 5206 A EATON 6406 EATON FS 5209 A		EATON FSO 10209 EATON FSO 10309 EATON FSO 4106 B EATON FSO 5206 B EATON V 4106 IVECO FSO 5206 B	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 223AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 44 ZF 6 AS 700 ZF 6 S 36 ZF 6 S 700 ZF 6 S 850			Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 224AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 100-1 MERCEDES G 100-12 MERCEDES G 100-13 MERCEDES G 100-2 MERCEDES G 100-9 MERCEDES G 140-6 MERCEDES G 140-8			Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00	
PTO Code 225AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 60-6 MERCEDES G 71-6 MERCEDES G 85-6 MERCEDES G 90-6			Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,20	


PTO Code 226AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model VOLVO MR 61 VOLVO MR 62 VOLVO R 6 VOLVO R 61 VOLVO R 62 VOLVO SR 52 VOLVO SR 61 VOLVO SR 62		Gear Type : Helis PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code 227AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	ZF 16 S 109 - 12.91 ZF 16 S 109 - 13.31 ZF 16 S 109 - 13.41 ZF 9 S 109 - 12.91 ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41	ZF 9 S 1110 - 12.73 ZF 9 S 1110 TD ZF 9 S 1115 / 12.73 ZF 9 S 1310 TO	Gear Type : Helis PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,00	
PTO Code 228AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model DAEWOO		Gear Type : Düz PTO Type : Single Gear Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 17,00	
PTO Code 229AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,10	
PTO Code 230AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model SCANIA GR 880 VOLVO GR 870 VOLVO GR 871 VOLVO GS 760 VOLVO GS 770 VOLVO GS 771		Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:2,00 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 20,00	

PTO Code 231AR	Pump Side Connection Type of PTO	Main Transmission Model MACK 5.08 MACK TRD 722		Gear Type : Flat PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Right and Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,80	
PTO Code 232AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	EATON ESO 14409 EATON FS 6109 A EATON FS 6109 B EATON FS 6109 DT EATON FS 6209 EATON FS 6209 EATON FS 6309 A EATON FS 8209 A	EATON FS 8209 B EATON FS 8209 EHD EATON FS 8309 A EATON FSO 6109 A EATON FSO 6109 A EATON FS 6109 AV	Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 318 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 233AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	EATON 3105 DT EATON 3106 DT EATON 4105 A EATON 4106 A EATON 5109 DT EATON 5206 A EATON 6406 EATON FS 5209 A	EATON FSO 10209 EATON FSO 10309 EATON FSO 4106 B EATON FSO 5206 B EATON V 4106 IVECO FSO 5206 B	Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 234AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 44 ZF 6 AS 700 ZF 6 S 36 ZF 6 S 700 ZF 6 S 850		Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 235AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 100-1 MERCEDES G 100-12 MERCEDES G 100-13 MERCEDES G 100-2 MERCEDES G 100-9 MERCEDES G 140-6 MERCEDES G 140-8		Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,50	

PTO Code 236AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 60-6 MERCEDES G 71-6 MERCEDES G 85-6 MERCEDES G 90-6		Gear Type : Helix PTO Type : Double Gear Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,70	
PTO Code 237AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model VOLVO MR 61 VOLVO MR 62 VOLVO R 6 VOLVO R 61 VOLVO R 62 VOLVO SR 52 VOLVO SR 61 VOLVO SR 62		Gear Type : Helix PTO Type : Double Gear Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,60	
PTO Code 238AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	ZF 16 S 109 - 12.91 ZF 16 S 109 - 13.31 ZF 16 S 109 - 13.41 ZF 9 S 109 - 12.91 ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41	ZF 9 S 1110 - 12.73 ZF 9 S 1110 TD ZF 9 S 1115 / 12.73 ZF 9 S 1310 TO	Gear Type : Helix PTO Type : Double Gear Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,20	
PTO Code 239AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 9 S 75		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00	
PTO Code 240AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 9 S 75		Gear Type : Helix PTO Type : Double Gear Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,00	


PTO Code 241AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2865 A IVECO 2865 S IVECO 2865.6		Gear Type : Helix PTO Type : Double Gear Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 242AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model IVECO 2865 A IVECO 2865 S IVECO 2865.6		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,50	
PTO Code 243AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 131-9 MERCEDES G 141-9 MERCEDES G 211-12 MERCEDES G 211-16 MERCEDES G 221-9 MERCEDES G 230-12 MERCEDES G 230-16 MERCEDES G 240-16	MERCEDES G 260-16 MERCEDES G 280-16 MERCEDES G 281-12 MERCEDES G 330-12	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 20,00	
PTO Code 244AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 155-16 MERCEDES G 155-9 MERCEDES G 180-16 MERCEDES G 210-16		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 17,60	
PTO Code 245AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	MERCEDES G 131-9 MERCEDES G 141-9 MERCEDES G 211-12 MERCEDES G 211-16 MERCEDES G 221-9 MERCEDES G 230-12 MERCEDES G 230-16 MERCEDES G 240-16	MERCEDES G 260-16 MERCEDES G 280-16 MERCEDES G 281-12 MERCEDES G 330-12	Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 17,00	



PTO Code 246AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 155-16 MERCEDES G 155-9 MERCEDES G 180-16 MERCEDES G 210-16		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 425 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,00	
PTO Code 247AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	ZF 16 S 151 IT ZF 16 S 181 IT ZF 16 S 1831 TD ZF 16 S 1920 IT ZF 16 S 1921 IT ZF 16 S 1921 TD ZF 16 S 2031 TO ZF 16 S 221 IT	ZF 16 S 2221 ZF 16 S 2221 IT ZF 16 S 2320 IT ZF 16 S 251 IT ZF 16 S 2521 IT ZF 16 T 181 IT	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 500 Power Kw : 52 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,60	
PTO Code 249AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 4 110 MERCEDES G 4 65 MERCEDES G 4 90 MERCEDES G 4 95 MERCEDES G 6 90		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code 250AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 4 110 MERCEDES G 4 65 MERCEDES G 4 90 MERCEDES G 4 95 MERCEDES G 6 90		Gear Type : Helix PTO Type : Double Gear Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,00	
PTO Code 251AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model EATON 14613 A EATON 11609 A EATON 11613 A EATON 12513 A EATON 14609 B EATON FS 10209 A EATON RT 9509 A FULLER		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00	

PTO Code 252BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MOY 9 F ISUZU MYY 5 A ISUZU MOYCR ISUZU MYY 5 T ISUZU MOYMR ISUZU MYY 6 P ISUZU MOYNA ISUZU MYY 6 S ISUZU MOYNC ISUZU MZZ 6 U ISUZUZ MOYNB ISUZU MZZ 6 W ISUZU MOYPZ ISUZU MOYUK		Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 170 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,03 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 254AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model SCANIA GR 900 SCANIA GRH 900 VOLVO GR 900 VOLVO GRH 900		Gear Type : Left Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:0,78 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 17,00	
PTO Code 255AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model VOLVO R 1400 VOLVO AT 2014 VOLVO R 1700 VOLVO V 2214 VOLVO SR 1700 VOLVO V 2514 VOLVO SR 1900 VOLVO VT 2214 VOLVO SR 2000 VOLVO VT 2214 B VOLVO SRO 2400 VOLVO VT 2514 VOLVO VT 2514 B		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,80	
PTO Code 256C	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	BÜTÜN KUYRUK TIPLİ PTO'larda POMPAYI MERKEZDEN KAÇIRMAK İÇİN KULLANILIR		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 500 Power Kw : 52 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Weight Kg. : 8,00	
PTO Code 257BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MITSUBISHI MO 15 S 5		Gear Type : Right Helix PTO Type : Single Gear Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,00	

PTO Code 258AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 14613 A EATON 11609 A EATON 11613 A EATON 12513 A EATON 14609 B EATON FS 10209 A EATON RT 9509 A FULLER	Gear Type : Helix PTO Type : Double Gear Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00	
PTO Code 259C	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	BÜTÜN KUYRUK TIPLİ PTO LAR DA POMPAYI ANA ŞANZIMAN GÖVDESİNDEN UZAKLAŞTIRMAK İÇİN PTO VE POMPA ARASINA TAKILIR.	Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Weight Kg. : 3,60	
PTO Code 260AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 S 151 ZF 16 S 1620 ZF 16 S 181 ZF 16 S 1820 ZF 16 S 1920 ZF 16 S 221 ZF 16 S 222 ZF 16 S 2220	ZF 16 S 251 ZF 16 S 2520 ZF 6 S 1000 ZF 9 S 1000 Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 4,50	
PTO Code 262BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model DAIHATSU DELTA	Gear Type : Left Helix PTO Type : Double Gear Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,14 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 263AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF S 5-42 4.65-0.772 ZF S 5-42 5.72	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	

PTO Code 263BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF S 5-42 4.65-0.772 ZF S 5-42 5.72		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	
PTO Code 264AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model SCANIA GRS 890 SCANIA GRS 900 SCANIA GRS 900 R SCANIA GRS 920 R		Gear Type : Left Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,10 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 18,70	
PTO Code 265BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 6 S 300 ZF 6 S 320 ZF 6 S 321 ZF 6 S 350		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,90	
PTO Code 268AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI HD 120		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 19 Output Ratio 1000 Rpm : 1:1,18 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00	
PTO Code 269AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	ZF 16 S 151 ZF 16 S 1620 ZF 16 S 181 ZF 16 S 1820 ZF 16 S 1920 ZF 16 S 221 ZF 16 S 222 ZF 16 S 2220	ZF 16 S 251 ZF 16 S 2520 ZF 6 S 1000 ZF 9 S 1000	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,60	





PTO Code 270AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 16 S 151 ZF 16 S 251 ZF 16 S 1620 ZF 16 S 2520 ZF 16 S 181 ZF 6 S 1000 ZF 16 S 1820 ZF 9 S 1000 ZF 16 S 1920 ZF 16 S 221 ZF 16 S 222 ZF 16 S 2220		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code 272AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model IVECO 2895 A IVECO 2895 B 9 IVECO 2895 S IVECO 2895 S 9 IVECO 2895 S 9 IVECO 2895.6 IVECO 2895.9		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 400 Power Kw : 42 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 273AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 S 151 IT ZF 16 S 2221 ZF 16 S 181 IT ZF 16 S 2221 IT ZF 16 S 1831 TD ZF 16 S 2320 IT ZF 16 S 1920 IT ZF 16 S 251 IT ZF 16 S 1921 IT ZF 16 S 2521 IT ZF 16 S 1921 TD ZF 16 T 181 IT ZF 16 S 2031 TO ZF 16 S 221 IT		Gear Type : Düz PTO Type : Single Gear - Cardan Shaft Torque Nm : 600 Power Kw : 62 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 4,50	
PTO Code 274AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 K 109 - 11.86 ZF 16 S 109 - 11.86 ZF 16 S 109 - 13,53 ZF 9 S 109 - 10.24		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 425 Power Kw : 44 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 16,10	
PTO Code 276BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model TATA T 5 TURBO		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:0,89 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 10,80	



PTO Code 277AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model SCANIA GR 905 SCANIA GRS 875 SCANIA GRS 895 SCANIA GRS 905 SCANIA GRS 905 R SCANIA GR50 905 SCANIA GR50 905 R		Gear Type : Left Helix PTO Type : Single Gear - Cardan Shaft - Double PTO Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side and Tail Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 21,00	
PTO Code 278AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2845.5 IVECO 2845.6 IVECO 2855.6		Gear Type : Helix PTO Type : Double Thread Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,00	
PTO Code 279AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model IVECO 2845.5 IVECO 2845.6 IVECO 2855.6		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 500 Power Kw : 52 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 10,50	
PTO Code 280AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 3 36 ZF 16 S 130 MERCEDES G 3 45 ZF 16 S 160 MERCEDES G 3 55 ZF 16 S 190 MERCEDES G 3 60 ZF 16 S 220 MERCEDES S 6-36 ZF 6 AS 1000 TO ZF 6 S 800		Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 5,00	
PTO Code 287AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model BMC 415 EURO 4 FOTON BJ 1069 JAC LC 6 T 46		Gear Type : Flat PTO Type : Double Thread Torque Nm : 160 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Right — (Pump Shaft Rotation : Left) Weight Kg. : 12,50	


PTO Code 288AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model VOLVO R 1400 VOLVO R 1700 VOLVO SR 1700 VOLVO SR 1900 VOLVO SR 2000 VOLVO SRO 2400 VOLVO AT 2014 VOLVO V 2214 VOLVO V 2514 VOLVO VT 2214 VOLVO VT 2214 B VOLVO VT 2514 VOLVO VT 2514 B		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 245 Power Kw : 25 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00	
PTO Code 289BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model I V E C O 2840.6 012A12 2840.6 013M11 2840.6 03M11 2840.6 03N11 2840.6 08N11 2840.6 13F11 2840.6 13P11 2840.6 17N11 2840.6 20611 2840.6 22L07 2840.6 20N09 ZF 6 S 380 ZF 6 S 400		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,30 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	
PTO Code 290AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MERCEDES G 56-6		Gear Type : Helix PTO Type : Double Thread Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code 291AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model MERCEDES G 56-6		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,00	
PTO Code 292AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU M 1 Z 08 ISUZU M 1 Z 11 ISUZU MOZ 06 ISUZU MOZ 79 ISUZU MOZ 85 ISUZU MOZ 92 ISUZU MOZ 95 ISUZU MZZ 5 L ISUZU MZZ 6 F ISUZU MZZ 6 U JAC LC 5 T 30		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,24 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,5	




PTO Code 292VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU M 1 Z 08 ISUZU M 1 Z 11 ISUZU MOZ 06 ISUZU MOZ 79 ISUZU MOZ 85 ISUZU MOZ 92 ISUZU MOZ 95 ISUZU MZZ 5 L ISUZU MZZ 6 F ISUZU MZZ 6 U JAC LC 5 T 30	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,24 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,5	
PTO Code 293VC3	Pump Side Connection Type of PTO Shaft End Coupled With Spline 6x21x25 - UNI	Main Transmission Model HYUNDAI CA 5-38 HA 01	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 170 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,03 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,5	
PTO Code 294AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 K 109 - 11.86 ZF 16 S 109 - 11.86 ZF 16 S 109 - 13,53 ZF 9 S 109 - 10.24	Gear Type : Helix PTO Type : Single Gear - Cardan Shaft Torque Nm : 500 Power Kw : 52 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,00	
PTO Code 295AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 K 109 - 11.86 ZF 16 S 109 - 11.86 ZF 16 S 109 - 13,53 ZF 9 S 109 - 10.24	Gear Type : Helix PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 500 Power Kw : 52 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type - Cardan Shaft Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 296AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2895 A IVECO 2895 B 9 IVECO 2895 S IVECO 2895 S 9 IVECO 2895 S 9 IVECO 2895.6 IVECO 2895.9	Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 380 Power Kw : 39 Output Ratio 1000 Rpm : 1:1,21 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,00	


PTO Code 297AEF	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> ZF 16 S 151 ZF 16 S 1620 ZF 16 S 181 ZF 16 S 1820 ZF 16 S 1920 ZF 16 S 221 ZF 16 S 222 ZF 16 S 2220	Gear Type : Flat PTO Type : Single Thread - Cardan Shaft Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 4,50	
PTO Code 298BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> HYUNDAI 5.38 / 0.722 HYUNDAI VT 3.5 T-C / 5 Vites	Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 150 Power Kw : 15 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,00	
PTO Code 299AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> DONG FENG	Gear Type : Flat PTO Type : Double Thread Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 301AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	<u>Main Transmission Model</u> ISUZU EYZ 51 ISUZU MJX 16 P	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,88 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,00	
PTO Code 304BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> ZF S 5-24	Gear Type : Flat PTO Type : Double Gear - Twin Gear Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,41 Mounting Location : Right Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	



PTO Code 305VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI M 1 S 5 HYUNDAI M 2 S 5 HYUNDAI M 3 S 5 MITSUBISHI M 1 S 5 MITSUBISHI M 2 S 5 MITSUBISHI M 3 S 5	Gear Type : Flat PTO Type : Single Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	
PTO Code 306VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI MO 35 S 5 MITSUBISHI MO 35 S 5 MITSUBISHI MO 35 T 6	Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 200 Power Kw : 21 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	
PTO Code 307VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MITSUBISHI MO 25 S5	Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	
PTO Code 308VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MITSUBISHI MO 15 S 5	Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	
PTO Code 309VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI 5.38 / 0.722 HYUNDAI VT 3.5 T-C / 5 Vites	Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 150 Power Kw : 16 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	


PTO Code 311AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MOY 9 F ISUZU MYY 5 A ISUZU MOYCR ISUZU MYY 5 T ISUZU MOYMR ISUZU MYY 6 P ISUZU MOYNA ISUZU MYY 6 S ISUZU MOYNC ISUZU MZZ 6 U ISUZUZ MOYNB ISUZU MZZ 6 W ISUZU MOYPZ ISUZU MOYUK		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,03 Mounting Location : Left Side Control System : Havalı PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11	
PTO Code 311VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MOY 9 F ISUZU MYY 5 A ISUZU MOYCR ISUZU MYY 5 T ISUZU MOYMR ISUZU MYY 6 P ISUZU MOYNA ISUZU MYY 6 S ISUZU MOYNC ISUZU MZZ 6 U ISUZUZ MOYNB ISUZU MZZ 6 W ISUZU MOYPZ ISUZU MOYUK		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,03 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11	
PTO Code 312BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model DAIMLER INDIA MO 36 S 6 MITSUBISHI MO 36 A 6 MITSUBISHI MO 36 S 6 MITSUBISHI MO 36 S 5		Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,50	
PTO Code 313VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HINO 350 5 S HINO LH 05 S HINO MG 06 HINO MG 10 S HINO MH 06 S TOYOTA LH 05		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 170 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
PTO Code 314VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MRP 58 P ISUZU MRP 59 ISUZU MSA 5 G ISUZU MSA 5 P ISUZU MSA 5 R		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 170 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,32 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,60	





PTO Code 315VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU 5 R W 530 ISUZU MXA 5 R ISUZU NXA 5 R		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,32 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,10	
PTO Code 316VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MSB 5 M ISUZU MSB 5 P ISUZU MSB 5 S		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,60	
PTO Code 317AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	RENAULT AT 2412 C RENAULT ATO 2612	VOLVO AT 26120 VOLVO DT 2412 C VOLVO V 2412 AT VOLVO V 2812 AT VOLVO VO 2512 AT VOLVO VO 3112 AT VOLVO VT 2412 B	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 530 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 318AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model SCANIA GR50 905 SCANIA GR50 905 R		Gear Type : Left Helix PTO Type : Single Gear - Cardan Shaft - Double PTO Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side and Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 21,00	
PTO Code 319VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model DAIMLER INDIA MO 36 S 6 MITSUBISHI MO 36 A 6 MITSUBISHI MO 36 S 6 MITSUBISHI MO 36 S 5		Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 150 Power Kw : 16 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,50	



PTO Code 321VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model MITSUBISHI MO 26 S 5 MITSUBISHI MO 26 S 5 A 025 MITSUBISHI MO 38 S 5 MITSUBISHI MO 38 S 5 A 002 MITSUBISHI MO 38 S 5 A 004 MITSUBISHI MO 38 S 6 MITSUBISHI MO 38 S 6 A 002		Gear Type : Right Helix PTO Type : Single Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 5,50	
PTO Code 322AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model AUMAN 10 T ISUZU FSR 33 L ISUZU FTR 10 ISUZU MLD 6 A ISUZU MLD 6 D		Gear Type : Left Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 450 Power Kw : 47 Output Ratio 1000 Rpm : 1:1,27 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 16,00	
PTO Code 323AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HINO LJ 06 S WLY 6 S 51 B - 33 - 00		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 340 Power Kw : 35 Output Ratio 1000 Rpm : 1:1,19 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,50	
PTO Code 325AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	RENAULT AT 2412 C RENAULT ATO 2612	VOLVO AT 26120 VOLVO DT 2412 C VOLVO V 2412 AT VOLVO V 2812 AT VOLVO VO 2512 AT VOLVO VO 3112 AT VOLVO VT 2412 B	Gear Type : Flat PTO Type : Single Thread Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,00	
PTO Code 326AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MOZ 79		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,67 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,50	

PTO Code 327AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 12 AS 1930 TD ZF 12 AS 2130 TD ZF 12 AS 2310 RETARDERLI ZF 12 AS 2530 TO ZF 16 AS 2601 RETARDERLI		Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 531 Power Kw : 55 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 13,00	
PTO Code 328VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HYUNDAI MIGHTY WIDE 6.701 / 0732 HYUNDAI T 060 S 6 MITSUBISHI TO 60 S 5		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,06 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,60	
PTO Code 329VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	DAIHATSU DELTA DAIHATSU H 260 DAIHATSU H 50 DAIHATSU M 150 DAIHATSU M 151 DAIHATSU M 153 DAIHATSU M 155 DAIHATSU M 52	HINO 300 HINO DUTRO	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:0,94 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,50	
PTO Code 330BE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HINO HN 15 M HINO M 500 HINO M 550		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 230 Power Kw : 24 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 17,00	
PTO Code 330VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model HINO HN 15 M HINO M 500 HINO M 550		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 230 Power Kw : 24 Output Ratio 1000 Rpm : 1:1,33 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 17,00	

PTO Code 331AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model EATON 475 SMA KAMAZ 14-100 KAMAZ 15-100 KAMAZ 53212 KAMAZ 5410 KAMAZ 54112 KAMAZ 55102 KAMAZ 5511	Gear Type : Flat PTO Type : Double Thread Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left and Right Side Control System : Pneumatic PTO Shaft Rotation : Right and Left - (Pump Shaft Rotation Direction: Left and Right) Weight Kg. : 15,00	
PTO Code 332AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model BMC 415 EURO 4 FOTON BJ 1069 JAC LC 6 T 46	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 170 Power Kw : 17 Output Ratio 1000 Rpm : 1:0,81 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 15,00	
PTO Code 333AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 12 AS 2131 TD ZF 12 AS 2331 TO ZF 12 AS 2831 RÖTARDERLİ ZF 16 S 221 TO	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal Torque Nm : 560 Power Kw : 63 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 12,60	
PTO Code 334VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model I V E C O 2840.6 012A12 2840.6 17N11 2840.6 013M11 2840.6 20611 2840.6 03M11 2840.6 22L07 2840.6 03N11 2840.6 20N09 2840.6 08N11 2840.6 13F11 ZF 6 S 380 2840.6 13P11 ZF 6 S 400	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,30 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00	
PTO Code 335VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model IVECO 2830.5 IVECO 5 S 200 IVECO 5 S 300 ZF 5 S 200 ZF 5 S 270 VO ZF 6 S 350	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 210 Power Kw : 22 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 11,00	


PTO Code 337AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model GAZ 236 GAZ 238 MAZ 236 MAZ 238 YAMZ 236 YAMZ 238		Gear Type : Flat PTO Type : Double Thread Torque Nm : 280 Power Kw : 29 Output Ratio 1000 Rpm : 1:1,30 Mounting Location : Right Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	
PTO Code 338BC7	Pump Side Connection Type of PTO SAE 10T 16/32 DP	ISUZU MOY 9 F ISUZU MOYCR ISUZU MOYMR ISUZU MOYNA ISUZU MOYNC ISUZUZ MOYNB ISUZU MOYPZ ISUZU MOYUK	ISUZU MYY 5 A ISUZU MYY 5 T ISUZU MYY 6 P ISUZU MYY 6 S ISUZU MZZ 6 U ISUZU MZZ 6 W	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 170 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,03 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 14,00	
PTO Code 339AEE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model EATON 475 SMA KAMAZ 14-100 KAMAZ 15-100		Gear Type : Flat PTO Type : Double Gear - Double Shaft Output Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,43 Mounting Location : Left and Right Side Control System : Pneumatic PTO Shaft Rotation : Right and Left - (Pump Shaft Rotation Direction: Left and Right) Weight Kg. : 12,00	
PTO Code 340VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 6 S 300 ZF 6 S 320 ZF 6 S 321 ZF 6 S 350		Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 14,00	
Pto Kodu 342VE	PTO'nun Pompa Tarafı Bağlantı Tipi 6 Keyway Milling Spindle Output 6x21x25 - UNI	Modeli 2840.6 / 013 M 13 2840.6 / 01 L 14 2840.6 / 012 A 12 2840.6 / 02 D 13 2840.6 / 02 L 15 2840.6 / 06 M 16 2840.6 / 11 A 17	Modeli I V E C O 2840.6 / 13 A 12 2840.6 / 14610 2840.6 / 16 E 13 2840.6 / 19 E 15 2840.6 / 19L17 2840.6 / 21 P 16 2840.6 / 24H15	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	

<u>PTO Code</u> 343BE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> HINO HN 15 M HINO M 500 HINO M 550	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 230 Power Kw : 24 Output Ratio 1000 Rpm : 1:0,78 Mounting Location : Left Side Control System : Mechanical PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 17,00	
<u>PTO Code</u> 344AD	<u>Pump Side Connection Type of PTO</u> Flanged - Coupling	<u>Main Transmission Model</u> MAZ	Gear Type : Flat PTO Type : Three Gear Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:0,71 Mounting Location : Side Control System : Pneumatic PTO Shaft Rotation : Weight Kg. : 20,00	
<u>PTO Code</u> 345AC2F	<u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36	<u>Main Transmission Model</u> SCANIA GRS 895	Gear Type : Left Helix PTO Type : Single Gear - Cardan Shaft - Double PTO Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Right Side and Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 21,00	
<u>PTO Code</u> 353VE	<u>Pump Side Connection Type of PTO</u> 6 Keyway Milling Spindle Output 6x21x25 - UNI	<u>Main Transmission Model</u> IVECO 2835.6	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,23 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 10,00	
<u>PTO Code</u> 355AC2 + AC2 355AC3 + AC3	<u>Pump Side Connection Type of PTO</u> Square Flange ISO 14 - DIN 5462 - 8x32x36 Shaft End Coupled With Spline 6x21x25 - UNI	<u>Main Transmission Model</u> MERCEDES EATON 475 SMA IVECO RENAULT VOLVO ZF	Gear Type : Helix PTO Type : Three Gear Torque Nm : 400 Power Kw : 41 Output Ratio 1000 Rpm : 1:1,28 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 23	

PTO Code 356AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ALVANT AUMARK C FOTON BJ 1061 OTOKAR ATLAS W1 LYYS 1B WAN LI YANG WANIER 6 S 51 B WLY 6 S 51 B - 40 A - 00	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 20 Output Ratio 1000 Rpm : 1:1,08 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13	
PTO Code 357AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model NISSAN MLD 62 T NISSAN MLS 62 T	Gear Type : Flat PTO Type : Double Thread Torque Nm : 240 Power Kw : 25 Output Ratio 1000 Rpm : 1:1,29 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 6,50	
PTO Code 358AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model FULLER 6 J 70 T MAZ 6 J 70 T	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 320 Power Kw : 33 Output Ratio 1000 Rpm : 1:1,56 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,00	
PTO Code 359AC3	Pump Side Connection Type of PTO Shaft End Coupled With Spline 6x21x25 - UNI	Main Transmission Model NISSAN MPS 62 T	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 280 Power Kw : 29 Output Ratio 1000 Rpm : 1:1,17 Mounting Location : Left Helix Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,00	
PTO Code 364AC2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ISUZU MZW 6 P ISUZU MW 02 B ISUZU MW00M-T1938805	Gear Type : Right Helix PTO Type : Three Gear Torque Nm : 280 Power Kw : 24 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 21,50	

PTO Code 365ADFM	Pump Side Connection Type of PTO Flanged - Coupling	Main Transmission Model ZF 9 S 75		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 950 - 800 - 680 - 450 - 400 Power Kw : 99 - 83 - 71 - 47 - 41 Output Ratio 1000 Rpm : 1.25 - 1.48 - 1.77 - 2.00 - 2.45 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 30,00	
PTO Code 366AD + C2FM	Pump Side Connection Type of PTO Flanged - Coupling + Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 16 S 109 - 12.91 ZF 9 S 1110 - 12.73 ZF 16 S 109 - 13.31 ZF 9 S 1110 TD ZF 16 S 109 - 13.41 ZF 9 S 1115 / 12.73 ZF 9 S 109 - 12.91 ZF 9 S 1310 TO ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 950 - 800 - 680 - 450 - 400 Power Kw : 99 - 83 - 71 - 47 - 41 Output Ratio 1000 Rpm : 1.25 - 1.48 - 1.77 - 2.00 - 2.45 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 30,00	
PTO Code 367AD + C3FM	Pump Side Connection Type of PTO Flanged - Coupling + Shaft End Coupled With Spline 6x21x25 - UNI	Main Transmission Model ZF 16 S 109 - 12.91 ZF 9 S 1110 - 12.73 ZF 16 S 109 - 13.31 ZF 9 S 1110 TD ZF 16 S 109 - 13.41 ZF 9 S 1115 / 12.73 ZF 9 S 109 - 12.91 ZF 9 S 1310 TO ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 950 - 800 - 680 - 450 - 400 Power Kw : 99 - 83 - 71 - 47 - 41 Output Ratio 1000 Rpm : 1.25 - 1.48 - 1.77 - 2.00 - 2.45 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 30,00	
PTO Code 367ADFM	Pump Side Connection Type of PTO Flanged - Coupling	Main Transmission Model ZF 16 S 109 - 12.91 ZF 9 S 1110 - 12.73 ZF 16 S 109 - 13.31 ZF 9 S 1110 TD ZF 16 S 109 - 13.41 ZF 9 S 1115 / 12.73 ZF 9 S 109 - 12.91 ZF 9 S 1310 TO ZF 9 S 109 - 13.31 ZF 9 S 109 - 13.41		Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 950 - 800 - 680 - 450 - 400 Power Kw : 99 - 83 - 71 - 47 - 41 Output Ratio 1000 Rpm : 1.25 - 1.48 - 1.77 - 2.00 - 2.45 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 30,00	
PTO Code 370C	Pump Side Connection Type of PTO ARA UZATMA			Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Weight Kg. : 5,5	 Boy 125,30 mm.

PTO Code 371C	Pump Side Connection Type of PTO ARA UZATMA		Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Weight Kg. : 5,00	 Boy 106,30 mm.
PTO Code 372AD + C2FM	Pump Side Connection Type of PTO Flanged - Coupling + Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 9 S 75	Gear Type : Helix PTO Type : Double Gear - Cardan Shaft Torque Nm : 950 - 800 - 680 - 450 - 400 Power Kw : 99 - 83 - 71 - 47 - 41 Output Ratio 1000 Rpm : 1.25 - 1.48 - 1.77 - 2.00 - 2.45 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 34,00	
PTO Code 374AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model BMC 415 JAC LC 6 T 55	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 170 Power Kw : 17 Output Ratio 1000 Rpm : 1:1,04 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 9,50	
PTO Code 375AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 12 TX 2210 TD ZF 12 TX 2620 TD ZF TRAXON 12 TX 2210 TD	Gear Type : Helix PTO Type : Double Gear - Pump Side Sealing Seal - Cardan Shaft Torque Nm : 350 Power Kw : 36 Output Ratio 1000 Rpm : 1:1,16 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 15,20	
PTO Code 376AC2F	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ZF 12 TX 2210 TD ZF 12 TX 2620 TD ZF TRAXON 12 TX 2210 TD	Gear Type : Flat PTO Type : Single Gear - Cardan Shaft Torque Nm : 420 Power Kw : 43 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 7,20	

PTO Code 379VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 6 S 420 V ZF 6 S 425	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,41 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 13,50	
PTO Code 380AE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ZF 6 S 500 TO OTOKAR ATLAS E6	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 180 Power Kw : 18 Output Ratio 1000 Rpm : 1:1,09 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 8,40	
PTO Code 381C2	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	BÜTÜN KUYRUK TIPLİ PTO LAR DA POMPAYI ANA ŞANZIMAN GÖVDESİNDEN UZAKLAŞTIRMAK İÇİN PTO VE POMPA ARASINA TAKILIR. (Uzun Tip)	Gear Type : Flat PTO Type : Single Thread - Pump Side Sealing Seal Torque Nm : 300 Power Kw : 31 Output Ratio 1000 Rpm : 1:1,00 Mounting Location : Tail Type Weight Kg. : 4,80	 Boy 125 mm.
PTO Code 383VC2M	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	Main Transmission Model ISUZU MOY 9 F ISUZU MOYCR ISUZU MOYMR ISUZU MOYNA ISUZU MOYNC ISUZUZ MOYNB ISUZU MOYPZ ISUZU MOYUK ISUZU MY 5 A ISUZU MY 5 T ISUZU MY 6 P ISUZU MY 6 S ISUZU MZZ 6 U ISUZU MZZ 6 W	Gear Type : Sol Helix PTO Type : Double Gear - Pump Side Sealing Seal - Switch Torque Nm : 250 Power Kw : 26 Output Ratio 1000 Rpm : 1:1,03 Mounting Location : Left Side Control System : Vacuum PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 16,20	
PTO Code 384VE	Pump Side Connection Type of PTO 6 Keyway Milling Spindle Output 6x21x25 - UNI	Main Transmission Model ISUZU MVC MOG 21 ISUZU MVC MOG 66	Gear Type : Left Helix PTO Type : Double Thread Torque Nm : 200 Power Kw : 21 Output Ratio 1000 Rpm : 1:1,06 Mounting Location : Left Side Control System : Pneumatic PTO Shaft Rotation : Rihgt — (Pump Shaft Rotation : Left) Weight Kg. : 12,00	

PTO Code 385AD	Pump Side Connection Type of PTO Flanged - Coupling	Main Transmission Model MERCEDES EATON FORD IVECO MAN RENAULT VOLVO ZF		Gear Type : Helix PTO Type : Three Gear Torque Nm : 940 Power Kw : 97 Output Ratio 1000 Rpm : 1:2,5 Mounting Location : Shaft Between Control System : Pneumatic PTO Shaft Rotation : Right and Left - (Pump Shaft Rotation Direction: Left and Right) Weight Kg. : 127,00	
PTO Code 387AC2M	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Switch Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,56 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,50	
PTO Code 388AC2M	Pump Side Connection Type of PTO Square Flange ISO 14 - DIN 5462 - 8x32x36	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Double Gear - Pump Side Sealing Seal - Switch Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,70 Mounting Location : Tail Type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 11,50	
PTO Code 390AD	Pump Side Connection Type of PTO Flanged - Coupling	MERCEDES G 3 36 MERCEDES G 3 45 MERCEDES G 3 55 MERCEDES G 3 60 MERCEDES S 6-36	ZF 16 S 130 ZF 16 S 160 ZF 16 S 190 ZF 16 S 220 ZF 6 AS 1000 TO ZF 6 S 800	Gear Type : Flat PTO Type : Four Gear - 4x4 Torque Nm : 550 Power Kw : 57 Output Ratio 1000 Rpm : 1:1,1 Mounting Location : tail type Control System : Pneumatic PTO Shaft Rotation : Left — (Pump Shaft Rotation : Right) Weight Kg. : 14,20	



+90 212 549 53 04 Pbx
 +90 212 549 53 08 - 09
 +90 533 960 33 60
 +90 532 554 16 36
 ptomms
 Pto Murat Makine+
 @PTOMURATMAKINA
 İkitelli Org.San.Bölg. Atatürk Bulv. Eskoop San.Sit. A2. Blok No.80 Başakşehir - İstanbul / TÜRKİYE

Turkey
 Discover
 the potential

